



Core & Coil (71A) MH 175W - 450W

CORE & COIL HID 71A5993001D

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information				
ANSI Code	M131-M171			
Lamp Type	350W MH			
Number Of Lamps	1 piece/unit			
Circuit Type	SUPER-CWA			
Ballast Type	Magnetic HID			
Base Model	71A5993A			
Core Size	4 1/4 x 4 3/4 (2 coil)			
Suitable For Outdoor Use	Yes			
Ignitor Catalog Number	LI533-H4			
Ignitor Temperature Rating	105°C			
Capacitor Value	22.5 MFD			
Capacitor Catalog Number	7C225P40			
Capacitor Requirements	345V			
Capacitor Temperature Rating	105°C			
Capacitor Diameter/Oval Dimensions	1.75 in			
Capacitor Height	4.8 in			
Automatic Restart	No			

Operating and Electrical	
Input Voltage	120/208/240/277 V
Input Frequency	60 Hz
Input Current (Open Circuit)	2.2/1.3/1.1/1 A
Input Current (Starting)	2.2/1.3/1.1/1 A
Input Current (Short Circuit)	1.75-2.65/1.0-1.55/0.9-1.35/0.75-1.15 A
Secondary Short Circuit Current	3.25-4 A
Constant Wattage Deviation	10%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Open Circuit Voltage	270 V
Input Current (Nom)	3.4/2/1.7/1.5 A A
Input Power (Nom)	400 W
Rated Lamp Power	350 W
Wiring	
Wire Striplength	0.5 mm
Wire Length By Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes


Datasheet, 2015, November 29 data subject to change

Core & Coil (71A) MH 175W - 450W

Max Ballast-Lamp Distance Remote Wiring	2'			
Recommended Fuse Value	10/7/5/5 A			
Annual and Analization				
Approval and Application				
Open Circuit Voltage Test (Volts)	240-300 V			
Approval Marks	ULR CSA certificate RoHS Compliant			
Temperature Marking	D/C/C/C			
UL Recognized	Yes			
Hipot Test (1 Minute)	2000 V			
Hipot Test (2 Seconds)	2500 V			
UL Insulation Class	H(180°C)			
UL Temperature Code	1029D			

Product Data	
Order product name	CORE & COIL HID 71A5993001E
EAN/UPC - Product	781087097502
Order code	913700535509
lumerator - Quantity Per Pack	1
lumerator - Packs per outer box	1
flaterial Nr. (12NC)	913700535509
Net Weight (Piece)	5.194 kg

Dimensional drawing



MH BAL 350W M131 QUAD KIT

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A5993001D	3.65 in	1.8 in	4.8 in	4.4 in	4.3 in	3.9 in

