

Presented By: iLightDepot/GELightingDepot
Contact Phone: 513-272-0800
Contact E-mail: sales@ilightdepot.com

Customer Name:
Project Name:
Fixture Type:





GE
Lighting

71445 - GEC226-MVPS-3W

GE CFL Multi-Volt ProLine™ Electronic Program / Rapid Start Ballast

- Multi-Voltage technology means a single ballast handles voltage from 108V to 305V
- Programmed starting for extended lamp life
- End-of-Lamp-Life Protection
- Color Coded Poke-In Connectors simplifies wiring
- 3-Way Ballast Kit (-3W) includes mounting plate, lead wires, extraction tool and mounting hardware for side exit, bottom exit or bottom exit with studs mounting



GENERAL CHARACTERISTICS

Application	2-CFQ26W, FT24 or 1-42W, CFTR32 3 Way Mounting Kit 120-277V Proline PS Compact Fluorescent
Category	Electronic - Program / Rapid Start
Ballast Type	Programmed start Series
Starting Method	10.0 %
Lamp Wiring	75.0 °C
Line Voltage Regulation (+/-)	Normal
Case Temperature (MAX)	Active
Ballast Factor	A (20-24 decibels)
Power Factor Correction	Metal
Sound Rating	Auto-restart/Thermally protected/Universal voltage
Enclosure Type	
Additional Info	

PRODUCT INFORMATION

Product Code	71445
Description	GEC226-MVPS-3W
Standard Package	Master
Standard Package GTIN	10043168714454
Standard Package Quantity	10
Sales Unit	Individual Pack
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168714457

DIMENSIONS

Case dimensions	
Length (L)	5.0 in(127.00 mm)
Width (W)	2.4 in(60.96 mm)
Height (H)	1.0 in(25.40 mm)
Mounting dimensions	
Bracket Length (BL)	NaN in(NaN mm)
Mount Length (M)	4.6 in(117.60 mm)
Mount Width (X or F)	NaN in(NaN mm)
Mount Slots (MS)	NaN in(NaN mm)
Weight	0.57 lb
Exit Type	Poke-in
Remote Mounting Distance	12.0 ft
Remote Mounting Wire Gauge	18.0 AWG

ELECTRICAL CHARACTERISTICS

Supply Current Frequency	50.0 Hz/60.0 Hz
--------------------------	-----------------

SAFETY & PERFORMANCE

- CSA
- UL Class P
- UL Listed
- UL Type 1 Outdoor
- UL Type CC
- UL Type HL
- FCC Part 18 Class B at 120 volts

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)(<=)	Crest Factor	THD% (<=)	Min. Starting Temp (°F/°C)
FT24W/4P	2	120	48	0.41 A	0.93	1.94	99	1.5	10.0	-20.0 °F / NaN
FT24W/4P	2	277	48	0.18 A	0.93	1.94	99	1.5	10.0	-20.0 °F / NaN
FC16T9	1	120	43	0.16 A	1.00	2.33	97	1.5	10.0	-20.0 °F / NaN
FC16T9	1	277	43	0.16 A	1.00	2.33	97	1.5	10.0	-20.0 °F / NaN
F24T5/HO	2	120	51	0.44 A	1.00	1.96	99	1.5	10.0	-20.0 °F / NaN
F24T5/HO	2	277	51	0.19 A	1.00	1.96	98	1.5	10.0	-20.0 °F / NaN

CFTR42W/4P	1	120	46	0.38 A	0.98	2.13	98	1.5	10.0	-20.0 °F / NaN
CFTR42W/4P	1	277	46	0.17 A	0.98	2.13	98	1.5	10.0	-20.0 °F / NaN
CFTR32W/4P	1	120	36	0.31 A	98.00	272.22	98	1.5	10.0	-20.0 °F / NaN
CFTR32W/4P	1	277	36	0.13 A	0.98	2.72	98	1.5	10.0	-20.0 °F / NaN
CFTR26W/4P	1	120	29	0.24 A	1.10	3.79	98	1.5	10.0	-20.0 °F / NaN
CFTR26W/4P	1	277	29	0.11 A	1.10	3.79	98	1.5	10.0	-20.0 °F / NaN
CFTR26W/4P	2	120	54	0.45 A	1.00	1.85	99	1.5	10.0	-20.0 °F / NaN
CFTR26W/4P	2	277	54	0.2 A	1.00	1.85	99	1.5	10.0	-20.0 °F / NaN
CFS21W/4P	2	120	51	0.42 A	1.12	2.20	99	1.5	10.0	-20.0 °F / NaN
CFS21W/4P	2	277	51	0.18 A	1.12	2.20	99	1.5	10.0	-20.0 °F / NaN
CFQ26W/4P	1	120	27	0.23 A	1.00	3.70	99	1.5	10.0	-20.0 °F / NaN
CFQ26W/4P	1	277	27	0.1 A	1.00	3.70	99	1.5	10.0	-20.0 °F / NaN
CFQ26W/4P	2	120	51	0.43 A	1.00	1.96	98	1.5	10.0	-20.0 °F / NaN
CFQ26W/4P	2	277	51	0.19 A	1.00	1.96	98	1.5	10.0	-20.0 °F / NaN

WARRANTY INFORMATION

GE Lighting warrants to the purchaser that each ballast will be free from defects in material or workmanship for period as defined in the attached documents from the date of manufacture when properly installed and under normal conditions of use.