




# LED BYPASS MODE TUBES



## PRODUCT FEATURES

- Retrofit / Bypass Mode (Type B)  
15W - Double and Single Ended  
17W - Double Ended
- Existing Fixture is Wired to Bypass the Ballast
- IP40 Rating
- Non-Dimming
- Low Thermal Decay
- No Mercury, Lead Free
- 100-277 Voltage Rating
- Film Coated Shatter Resistant Glass Tube
- Frosted
- 50,000 Hour Lifetime Rating
- NSF Certified
- DLC Listed
- UL Classified
- G13 Mounting
- Low Maintenance
- No UV Emission
- 5-Year Limited Warranty
- Operating Temperature Range:  
-4°F to 122°F (-20°C to 50°C)

## PRODUCT SPECIFICATIONS

MODEL	POWER (W)	LUMENS (LM)	CCT (K)	DIMENSIONS (IN)	EFFICIENCY (lm/W)	BEAM ANGLE
CLT98-15WT8F-B <sup>1</sup>	15	2100	4000 / 5000	48.0	136	240°
CLT98-17WT8F-B <sup>2</sup>	17	2300	4000 / 5000	48.0	136	240°

<sup>1</sup> Double and Single Ended

<sup>2</sup> Double Ended

