WAC LIGHTING

Whirl

Mini Light 4CCT

•					
Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-19408 8"	2700K 3000K 3500K 4000K	BK Black	21 W 21 W 21 W 21 W	1103 1103 1103 1103	1027 1027 1027 1027 1027

Example: PD-19408-40-BK

For custom requests please contact customs@waclighting.com

DESCRIPTION

Like a tornado whirling in space, multiple curves of illumination are backed by a black frame and suspended from a cloud-like canopy. Integrated LEDs provide crisp, clean light tomodern spaces.

FEATURES

• Low profile, adjustable powered aircraft cables for an ultra-clean look

- May be mounted on a sloped ceiling
- Built in color temperature adjustability. Switch from
- 2700K/3000K/3500K/4000K
- · Option to pre-select color temperature or adjust in the field
- Spin-on round canopy with minimal hardware
- Driver concealed within the canopy

SPECIFICATIONS

Color Temp:	4000K,3000K,2700K,3500K	
Input:	120/277V,50/60Hz	
CRI:	90	
Dimming:	ELV: 100-10% ,TRIAC: 100-5%	
Rated Life:	50000 Hours	
Standards:	ETL, cETL	
	Damp Location Listed	
Construction:	Aluminum body with silicon diffuser	

Fixture Type:

Catalog Number:

Project:


Location:

FINISHES:



Black

LINE DRAWING:



PD-19406

waclighting.com | Phone (800) 526.2588 | Fax (800) 526.2585 | Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. October 2024